PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2000-057790

(43)Date of publication of application: 25.02.2000

(51)Int.CI.

G11C 16/06 H01L 27/04 H01L 21/822 H02M 3/07

(21)Application number: 10-221736

(71)Applicant: RICOH CO LTD

(22)Date of filing:

05.08.1998


(72)Inventor: ITSUSHIKI KAIHEI


(54) VOLTAGE-GENERATING CIRCUIT

(57)Abstract:

PROBLEM TO BE SOLVED: To boost a voltage without increasing a chip area and without entailing a voltage step-up loss due to a back bias effect.

SOLUTION: A gate electrode 106 of a polysilicon film is formed like teeth of a comb by a minimum line width and a minimum distance regulated by a design rule via a gate oxide film 119 on an N type well 102 formed to a P type silicon substrate 101. An N type impurity region 104 is formed except below the gate electrode 106 to the well 102 in the periphery of the gate electrode 106. In this arrangement, influences of a parasitic resistance and a parasitic capacitance of the well 102 can be eliminated. Although an area where the well 102 faces the gate electrode 106 is made approximately half, a capacitance between end parts and side walls of the gate electrode 106, and the well 102 and a contact metal 120 increases and therefore a total capacitance hardly decreases.





LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of

rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office